

# Rich pigment blends for full depth colouring of premix and precast concrete



COLOURS FOR GREY CONCRETE • COLOURS FOR GREY CONCRETE

CCS OYSTER	CCS PEWTER	CCS BRICK RED
CCS GHOST GUM	CCS ALPINE	CCS ULURU
CCS ONYX 21	CCS PAPERBARK	CCS MULBERRY
CCS BLACK 21	CCS SPINIFEX	CCS CABERNET
CCS BLUESTONE	CCS GECKO	CCS JARRAH
CCS LIQUORICE	CCS MYSTERY	CCS CHOCOLATE
CCS PANTHER	CCS DRIFTWOOD	CCS KELP

COLOURS FOR GREY CONCRETE • COLOURS FOR GREY CONCRETE

CCS CANVAS	CCS PUMICE	CCS SUNTAN
CCS DESERT BUFF	CCS JURASSIC	CCS BISCUIT
CCS YORK STONE	CCS LYCHEE	CCS CARAMEL
CCS MOROCCO	CCS MANGROVE	CCS GIPSY
CCS HONEYCOMB	CCS FIG	CCS TOBACCO
CCS BREADCRUMB	CCS LIZARD SKIN	CCS POTTERY
CCS SANDPLAIN	CCS CIGAR	CCS MEXICO

COLOURS FOR GREY CONCRETE • COLOURS FOR GREY CONCRETE

CCS RAFFIA BEIGE	CCS BONSAI	CCS STONE BEIGE
CCS LIMESTONE	CCS EUCALYPTUS	CCS FUDGE
CCS CORN	CCS KAKADU	CCS EARTH BROWN
CCS GOLDEN BRONZE	CCS CACTUS	CCS GRAPE

COLOURS FOR GREY CONCRETE

COLOURS FOR OFF-WHITE CONCRETE		
CCS KINGFISHER	CCS POLLEN	CCS CASHMERE
CCS SNOW	CCS PORCELAIN	CCS MACADAMIA

Please note that your concrete supplier may not be able to provide the above colours unless they have 'off-white' cement available at the nominated plant.

**How to duplicate the CCS colours displayed in this chart in concrete**  
 Trowel finished concrete in the above colours can be produced by adding one pre-formulated bag of CCS Pigment Concentrate for each cubic metre of 20/25 MPa strength concrete. Higher strength concrete will require the larger CCS bags. Due to regional differences in cement and aggregates, as well as slump and finishing techniques, (such as exposed aggregate and honed finishes) variations to the above colours can occur. **Where an exact colour is essential, representative job samples using the intended raw materials and finishing techniques should be completed and then inspected once the sample has cured for 14-30 days.** Please refer to the 'Guidelines For Use' Data Sheet (available at [www.concretecoloursystems.com.au](http://www.concretecoloursystems.com.au) or by phoning 1800 077 744) for suggested placement methods.

**Suggested Specification**  
 Concrete is to be integrally coloured with Concrete Colour Systems \_\_\_\_\_ Pigment Concentrate (ph. 1800 077 744 or closest city ph. no.).  
 One pre-formulated bag is to be added for each cubic metre of \_\_\_\_\_ MPa, using \_\_\_\_\_ cement. All surfaces should be finished uniformly – do not over-trowel. Do not cure with plastic sheeting, membrane paper or intermittent wetting and drying. Caution should be taken to ensure any curing compound is suitable for both structural and aesthetic purposes.



**brilliant colours**  
**outstanding results**